



Available Colors: Navy, Charcoal, Brown, Red/Black, Hunter Green and Burgundy



**B**oulevard™ has a unique high-low wave design of alternating Decalon® drying yarn and Decalon® yarn wrapped with a tough mono-filament for ultra-aggressive scraping. The wave pattern runs across the mat and against foot traffic. 40 ounces of tufted yarn per square yard offer the ultimate in moisture absorption and crush resistance for use in the heaviest traffic areas. Boulevard™ has a heavyweight vinyl backing available in corresponding colors to ensure minimum mat movement and enhance the aesthetic appeal of the mat.


Test	Test Description	*Results
ASTM D-6540-00	Accelerated Soiling of Pile Yarn	Rating After Vacuum 4.5 Rating After Extraction 5.0
ASTM D412	Breaking Load and Elongation	316.7 lbs/in <sup>2</sup>
ASTM D5252-98a	Accelerated Wear - 4,000 cycles (Hexapod Tumble Drum Tester)	Appearance: 2.7 Color: 3.0
ASTM D3936-0	Delamination	Exceeds Backing Strength
CPSC FF 1-70 (ASTM D-2859)	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass
-	Water Retention	Weight Gain = 235.15% (0.882 gals./yd <sup>2</sup> )
ASTM D2240-02	Durometer Hardness	70
ASTM D1335-98	Tuft Bind of Pile Yarn	7.3 = Standard

\*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.

07/2014

Appearance Rating Key	
5	No change
4	Slight change
3	Noticeable change
2	Considerable change
1	Severe change

- 40 oz. Face Weight
- Thickness: 3/8"
- Heavyweight vinyl non-slip backing
- Stock Sizes: 2' x 3', 3' x 4', 3' x 5', 3' x 6', 3' x 10', 4' x 6', 4' x 8'
- Roll Sizes: 3' x 60', 4' x 60', 6' x 60'
- Custom Sizes: In 3', 4', and 6' widths (up to 60')
- Recommended and approved product as part of the GreenTRAX™ program for "Green Cleaning" environments



Custom Sizes