



**Specialty**



**S**afety Message Mats make your safety message loud and clear while keeping facilities cleaner and safer. Pre-printed message mats warn employees who may be entering a hazardous area, may need special ear or eye protection, or just act as a reminder to think and act safely in work environments. Pre-printed message mats offer functionality as an entrance mat cleaning dirt and moisture from shoes and keeping facilities cleaner and safer.



Test	Test Description	*Results
ASTM D1894-08	Static and Kinetic Coefficients of Friction	Painted Concrete: Avg. Load 32.3 lbs; COF 0.65 Epoxy Concrete: Avg. Load 31.5 lbs; COF 0.63 VCT: Avg. Load 35.9 lbs; COF 0.72 Vinyl Sheet: Avg. Load 27.7 lbs; COF 0.55
ASTM D-5252-98	Accelerated Wear - 4,000 cycles (Hexapod Tumble Drum Tester)	Appearance: 3.2 Color: 3.0
ASTM D6540-00	Accelerated Soiling	Based on Visual Inspection 1.0 - Vacuum Rating 3.0 - Rating After Extraction
CPSC FF 1-70 ASTM D-2859	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass
ASTM D412-06	Breaking Load and Elongation	225.6 lbs/Inch <sup>2</sup>
ASTM D3936-05	Delamination	Construction would not allow for delamination
ASTM D2240-02	Durometer (Hardness)	75
ASTM D1335-05	Tuft Bind	9.0 lbs.

\*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.

07/2014

Appearance Rating Key

5	No change
4	Slight change
3	Noticeable change
2	Considerable change
1	Severe change

- 24 oz. face weight - Cut Pile
- 14 pre-printed messages to choose from
- Select messages also available in Spanish
- PVC Vinyl non-slip backing - 70 Mils
- Overall thickness - 5/16"
- Stock Sizes: 3' x 5', 4' x 6'

