



Available Colors: Black



Superfoam Comfort® takes comfort and ergonomic support to the next level. It's made from a full 3/4" thick softer PVC/ Nitrile rubber foam blend that offers greater resistance to a variety of chemicals, cutting fluids, greases, oils and fats. The high-density materials in Superfoam Comfort® incorporate millions of tiny closed cells that won't absorb liquids. It's extreme comfort and lightweight make it the perfect mat for use in areas where mats are regularly moved for cleaning. Superfoam Comfort® also comes in a perforated version with a small hole drainage system for the removal of liquids and debris from the work area.

Test	Test Description	*Results
-	Compression Deflection	@ 20 lbs/in ² : 0.302 @ 40 lbs/in ² : 0.445
ASTM D-1004-94a-03	Tear Strength	13.1 lbs
ASTM D-2240	Durometer (Shore A)	10
ASTM D-3884	Abrasion Resistance	@ 500 cycles: 14.8% @ 1000 cycles: 25.7%
ASTM D-2859/CPSC FF-170	Surface Flammability/Carpets and Rugs	Pass
ASTM D-1894-01	Modified Slip Test: Avg. C.O.F. (Coefficient of Friction)	VCT: 0.73 Painted Concrete: 0.73 Vinyl Flooring: 0.66 Epoxy Painted Concrete: 0.83
ASTM D-412	Breaking Load & Elongation	Breaking Load - 45.4 lbs/in ² Elongation - 103.04%
ASTM E-648	Critical Radiant Flux	Watts per Cm ² : 0.67

*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.

- PVC/Nitrile rubber foam blend
- Extra soft material for greater support
- Oil and grease resistant
- Closed cell construction won't absorb liquids
- All four sides beveled to minimize trip hazards
- Non-allergenic, Silicone-free compound
- Thickness: 3/4"
- Stock Sizes: 3' x 2', 3' x 3', 3' x 5', 3' x 8'
- Roll Sizes: 2' x 75', 3' x 75', 4' x 75'
- Custom Sizes: 2', 3', and 4' widths (up to 75')



Custom



Food Service



Drainage (441)



Anti-Fatigue



Oil Resistant



Anti-Slip

